



## Ducati Scrambler Desert Sled

Engine	
Type	L-Twin, Desmodromic distribution, 2 valves per cylinder, air cooled
Displacement	803 cc
Bore x stroke	88 x 66 mm
Compression ratio	11:1
Power	75 hp (55 kW) @ 8,250 rpm
Torque	50 lb-ft (68 Nm) @ 7,750 rpm
Fuel injection	Electronic fuel injection, 50 mm throttle body
Exhaust	Stainless steel muffler with catalytic converter and 2 lambda probes, aluminium tail pipes
Standard	Euro 4
Consumption and emissions	5.1 l/100 km - CO2 119 g/km
Transmission	
Gearbox	6 speed
Ratio	1=32/13 2=30/18 3=28/21 4=26/23 5=22/22 6=24/26
Primary drive	Straight cut gears, Ratio 1.85:1
Final drive	Chain, front sprocket 15, rear sprocket 46
Clutch	APTC wet multiplate with mechanical control
Chassis	
Frame	Tubular steel Trellis frame
Front suspension	46 mm fully adjustable USD forks
Front wheel travel	200 mm (7.9 in)
Front wheel	Spoked aluminium wheel 3.00" x 19"
Front tyre	Pirelli SCORPION™ RALLY STR 120/70 R19
Rear suspension	Kayaba rear shock, pre-load and rebound adjustable. Aluminium double-sided swingarm
Rear wheel travel	200 mm (7.9 in)
Rear wheel	Spoked aluminium wheel 4.50" x 17"
Front tyre	Pirelli SCORPION™ RALLY STR 170/60 R17
Front brake	330 mm disc, radial 4-piston calliper with ABS as standard equipment
Rear brake	245 mm disc, 1-piston floating calliper with ABS as standard equipment
Dashboard	LCD
Dimensions and weight	
Wheelbase	1,505 mm (59.3 in)
Rake	24°
Trail	112 mm (4.4 in)
Total steering lock	35 °
Fuel tank capacity	13.5 l - 3.57 gallon (US)
Dry weight	191 kg (421 lb)
Wet weight*	207 kg (456 lb)
Seat height	860 mm (33.9 in) - low seat 840 mm (33.0 in) available as accessory
Max height	1,213 mm (47.8 in) (brake reservoir)
Max width	940 mm (37.0 in) (mirrors)
Max length	2,200 mm (86.6 in)
Number of seats	Dual seat
Standard equipment	Steel tank with interchangeable aluminium side panels, headlight with homologate grill, LED light-guide and interchangeable aluminium cover, LED rear light with diffusion-light, LCD instruments with interchangeable aluminium cover, machine-finished aluminium belt covers, under-seat storage compartment with USB socket, aluminium handlebar with cross-strut, front stem protectors, seat with specific design, high front mudguard, long rear mudguard and high plate support
Warranty	
	24 months unlimited mileage
	12,000 km (7,500 miles) / 12 months
	12,000 km (7,500 miles)

\*Kerb weights indicate total bike weight with all operating consumable liquids and a fuel tank filled to

The power values indicated above are measured using a chassis dynamometer. Homologated power data, as quoted in the Bike Registration Document, are measured using an engine dynamometer according to the homologation regulation. The two power values may differ because of the different measurement equipments.